

TECHNICAL DATA SHEET

TRUE HIGH PERFORMANCE ENGINE OIL

SAE 15W 40 API: SL/CI-4

TRUE MULTI-FLEET ENGINE OIL

Description

TRUE HIGH PERFORMANCE MULTI-FLEET API: SL/CI-4 is an engine oil blended from virgin base oils, which has been fortified with High Performance Additives to meet the API SL/CI-4 specification and associated OEM approvals.

Outstanding Features

TRUE HIGH PERFORMANCE MULTI-FLEET API: SL/CI-4 meets or exceeds the following specifications:

- API SL/CI-4
- ACEA E5-2002
- MB 228.3
- VOLVO VDS 3
- MACK EOM PLUS
- MAN 3275
- CUMMINS 20078

Application

TRUE HIGH PERFORMANCE MULTI-FLEET API: SL/CI-4 oils are recommended for naturally-aspirated and turbo charged diesel engines as well as petrol engines calling for API classification SL & CI-4. It can also be used in a variety of other industrial applications, such as certain types of compressors where the manufacturer specifies the use of engine oil. Also to be used in forklifts, etc.

Technical Data

SAE grade	15W-40
Viscosity @ 40°C	110
Viscosity @ 100°C	14.5
Viscosity Index	120
Pour Point °C	-25

Pack Sizes

210L	Drum
20L	Pail
5L	Bottle

Technical Data Reviewed 01/01/2020

MANUFACTURED AND PACKED IN AN ACCREDITED FACILITY

info@naudechemicalandenergy.com www.naudechemicalandenergycompany.com